





NOTE:
 2x6 STUD CONSTRUCTION
 E/FIRE RATED TYPE X
 DRYWALL ON ALL HOUSE/
 GARAGE CONNECTIONS

FIRE RATED
 SELF CLOSING
 STL. DOOR
 20 MIN. RATING

SLOPE SLAB @ 1/8" PER FT.

TYPICAL GARAGE FLOOR:
 3 1/2" CONCRETE SLAB w/
 6x6 16/16 W/CHD W/IRN TRNK
 CONCRETE GARAGE WALLS WILL
 SLOPE CONC. TOWARDS DOOR
 @ 1/8" PER FT.

2 STALL GARAGE
 25'-5" X 31'-3"

SLOPE SLAB @ 1/8" PER FT.

ENGINEERED TRUSSES
 24' O.C.

NOTE:
 - ALL WINDOWS, PATIO DOORS
 ON THIS PRINT ARE MARVIN
 INTEGRITY
 - VERIFY OWNER FOR FRONT
 DOOR PLACEMENT OF
 WATER/ELEC. METERS
 - 8'-1 1/2" PLT. HEIGHT THRU OUT
 10' BLK WALL
 CONTRACTOR TO VERIFY ALL
 DIMENSIONS AND CONDITIONS
 IN FIELD AND BE RESPONSIBLE
 FOR SAME

FUTURE INDOOR POOL